Smart Mobile Terminal

SUNMI L2Ks

Define a new classic for indoor applications and beyond.

Powered by **SUNMI OS** | Compatible with **SUNMI DMP** | G **Google Mobile Services**

Better Protection Ratings

To withstand everyday usage, L2Ks is 1.8m drop resistant, IP68 rated and has passed 3000 0.5m tumble tests.

ATL Large-capacity Battery, Safe And Durable

Equipped with a ATL battery cell, L2Ks features 800 charge cycles. The removable 5000mAh large-capacity battery can stand for up to 2 shifts.

Professional Scan Engine

High speed — 10 scans/sec; long reach — up to one meter read distance; accurate — read just the barcode the laser aimer positioned; reliable — quickly read hard-to-read barcodes including scratched, stained, crinkled barcodes or DPM barcodes, etc.

| **Hand Strap** | **Charging Base** | **Four-slot Battery Charger** | **Screen tempered glass** | **Trigger Handle** | **Protective Case** |

SUNMI L2Ks Tech Specs

Model Approved T8A10	**OS** SUNMI OS (*based on Android 11)	**CPU** Octa-core processor	**Memory** 4GB RAM+32GB ROM 2GB RAM+16GB ROM (Not supported for GMS Version)	**Display** 4"HD, 800x480 Capacitive IPS
Camera No GMS Version: Rear: 8MP AF GMS Version: Rear: 13MP AF Front: 5MP FF Rear camera for 1D / 2D barcode scanning	**NFC (optional)** Supports TypeA&B card, Mifare card, Felica card; ISO/IEC 14443 and ISO15693 compliant	**Speaker** 2* 1W	**PSAM Card Slot** 1*PSAM (optional)	**SIM Card Slot** 1* NANO SIM+1* SIM+ 1* MicroSD (TF)
	Communication 4G/3G/2G	**Wi-Fi** 2.4GHz/5GHz IEEE 802.11 ac/a/b/g/n/d/ e/h/i/j/k/r/v/w	**Bluetooth** Bluetooth 5.0 BLE	**GPS** AGPS GPS/Glonass/Beidou/ Galileo
Sensors Light sensor, proximity sensor, gravity sensor, gyroscope (optional), hall sensor (optional), E-compass (optional)	**Buttons** 1* Function button 2* Left and right scan buttons 23* Physical buttons	**Microphones** 2* MIC	**Ports** 1*Type-C, support OTG 2*pogo pin at the bottom for charging 8* pogo pin on the back for accessories	**Battery** Removable polymer lithium battery, 3.8V/5000mAh
vSIM Only support China mainland	**Dimensions (L*W*H)** 160×64.5×14.4mm	**Total Weight** 243.5g	**Protection** IP68 1.8m drop spec	**Environment** Operating temperature: -20℃~55℃ Storage temperature: -40℃~70℃
Power Adapter Type-C 5V/2A, 9V/2A	**Scanner** Professional scan engine (*Zebra & Honeywell are optional)	**Accessories (optional)** Trigger handle Charging base Four-slot battery charger Hand strap Screen tempered glass		